



**LEGEND**

- SURFACE MOUNTED INCANDESCENT
- WALL MOUNTED INCANDESCENT
- ◻ RECESSED INCANDESCENT
- ⊕ EXHAUST FAN VENTED TO EXTERIOR
- ⊖ CEILING MOUNTED DUPLER OUTLET
- ⊕ SPRT W/ WIRE TO SWITCH
- ⊕ SINGLE POLE SWITCH
- ⊕ THREE-WAY SWITCH
- ⊕ TELEPHONE OUTLET
- ⊕ TELEVISION OUTLET
- 10V SMOKE ALARM / DETECTOR WITH BATTERY BACKUP-INNOCENT
- 110V CARBON MONOXIDE ALARM / DETECTOR WITH BATTERY BACKUP-INNOCENT
- ⊕ PEET RETURN OF WATER IN BEDROOM DOOR
- ⊕ STRUCTURAL BEAM SEE INCLUDED CALCULATIONS FOR BEAM DATA

**NOTES**

1. VENT RANGE HOOD & BATH FANS TO OUTSIDE
2. METAL GAS FIREPLACE INSTALL PER MANUF SPECS. PROVIDE OUTSIDE COMB AIR
3. PROVIDE 18" HIGH PLATFORM FOR WATER HEATER & FURNACE
4. SERVIC STRAPPING OF WATER HEATER IS REQUIRED PER SECTION M39.2

**INTERIOR BEARING WALL**  
 ■ BEARING POINT LOCATION PROVIDE SOLID BEARING WALL MEMBER WITH UNLESS NOTED

**NOTES**  
 \*\*SHEARWALL/HOLD-DOWN CALLOUT, SEE ENGINEERING "S" PAGES FOR TYPES REQUIRED.